

## Notice Inviting Tender

### High Court of Jharkhand, Ranchi

Ref. No.

Dated: 26.07.2024

Sealed Tenders are invited from the reputed firms for the purchase of 95 numbers of revolving Computer Chairs and 95 numbers of Computer Tables for this Court.

**Table-A (revolving Computer Chair)**

Computer Chair	Specification
Locking mechanism	Tilt limiter
Armrest type and arm movement	Fixed
Seat depth adjustment	Fixed type
Backrest Type	Tilting type
Back rest support type	Contoured back
Headrest type	Without headrest
Revolving mechanism	Designed with 360 degree revolving type and upright locking
Height adjustments	Pneumatic
Pedestal Base	Aluminium die cast
Twin wheel castor material	Nylon
Number of twin wheel castor	5 nos.
Minimum diameter to twin wheel castor	50 mm
Armrest Material	MS arm with ABS arm top
Seat base material	Host Pressed plywood
Seat material	PU foam
Minimum density of foam used in seat	30kg per cubic meter
Minimum thickness of PU foam used in seat	30 mm
Seat upholstery	Mesh fabrics
Backrest base frame material	Thermoplastic elastomer frame with insert in two-piece
Backrest upholstery material	Mesh fabrics
Upholstery material thickness/fabric substance used in seat/backrest	Minimum 200 GSM (for Woven fabric)
Minimum seat height from floor surface	400 mm
Minimum seat height adjustment	Upto 100 mm
Minimum width of seat	500 mm
Minimum depth of seat	450 mm
Minimum width of backrest	450 mm
Backrest height	Low back (350 to 450 mm)
Minimum thickness of MS Plate joining the understructure with seat	2 mm
Minimum Pedestal size (diameter)	650 mm
Upholstered material seat colour	Black
Upholstered material backrest colour	Black
Warranty	01 year
Green Pro Certification issued by CII	Yes
BIFMA membership	Yes

**Table-B (Computer Table)**

Computer Table	Specification
Structure/Frame of table	Gable end and modesty panel
Frame Type	Freestanding
Accessories/Optional requirement for table	Internet point
The type of storage provided	One side pedestal unit
Keyboard type	Provided
Foot rest	Not provided
Mode of supply	Knocked down to be assembled at consignee site by the seller
Tabletop material	Prelaminated particle board (wood product) of grade II type II of IS 12823/Late
Thickness of tale top material (+- 1 mm)	19 mm
Gable end material	Three Layer prelaminated particles board (wood product) of grade II type III of IS 12823/latest
The thickness of the modesty panel	15 mm

	12823/latest
The thickness of the modesty panel plain side	15 mm
Gable end and modesty panel plain side	Edge to be banded with PVC tape 2 mm thick with the help of hot melt glue
Table to edges	Edge to be banded with PVC tape with 2 mm thick with the help of hot melt glue
Beam material	CRC 40 mm X 40 mm square pipe with powder coated
Width of table top +- 10 mm	1200 mm
Depth of table +- 10 mm	600 mm
Height of table +- 10 mm	750 mm
Total number of drawers/storage in pedestal units	Three drawers
Complete body facia and drawer material in pedestal unit	Three layers of prelaminted particles board (wood product) of grade II type of IS 12823/latest
Thickness of the complete body fascia drawer material	15 mm
Material for back	Three layers of prelaminted particle board (wood product) of grade II type of IS 12823/lates
Back panel thickness in pedestal unit	11 mm
Drawer Bottom material	Three layers of prelaminted particle board (Wood product) of grade II type II of IS 12823/latest
Drawer bottom material thickness	11 mm
Provision of castor in pedestal unit	Without
Lock provided (pedestal unit)	Central lock
Pedestal handle material	Chrome plated
Pedestal outer finish	Laminated in colour with swede finist 0.6 – 0.8 mm thickness of type S, F or P having index no. 3.2.3. conforming to IS 2046/lates with having balancing laminate of 0.5 mm thick on another side
Width of pedestal unit in mm (+- 10 mm )	610 mm
Depth of pedestal unit (+- 10 mm )	450 mm
Height of pedestal unit (+- 5 mm)	725 mm
Material of keyboard tray and right angle L-type supporting backrest	Plastic PVC Sheet of standard quality
Material thickness of keyboard tray +- mm	12 mm
Fixing of supporting bracket	With telescopic
Length of telescopic channel +- 10 mm	200 mm
Keyboard height	100 mm
Keyboard front width +- 10 mm	500 mm
Keyboard depth +- 10 mm	350 mm
Colour and finish table top finish	Lamination in clour with swede finish 06.- 0.8 mm thickness of type S, F or P having index 3.2.3 conforming to IS 2046/latest with having balancing laminate of 05. Mm thick on another side
Warranty period	05 years
The product has BIFMA certification	Yes
OEM of the offered product is ISO 901: 2015 certified	Yes

Sealed tenders are to be submitted in the office of the undersigned on or before 16.08.2024 till 4:30 p.m. The tender should contain the following specifications:

1. Price quoted must be inclusive of GST.
2. Catalogues with details of the items are must.
3. maximum time required for supply of the articles must be specifically mentioned.

**Note**

- a. No tender will be entertained after the due date.
- b. Any further details if required may be collected from the Office of the undersigned on any working days during 10:30 am – 03:30 pm (Monday to Saturday)

c. The Court reserves the right to accept or reject any or all tenders without assigning any reasons.

-Sd/-

**Registrar (Establishment)**  
**High Court of Jharkhand, Ranchi**